Airflow

Fresh air volume				
Indoor	Туре	ECM centrifugal		
	CFM	160-290		
	Supply connection	Integrated front		
	Return connection	Integrated bottom		
	Speeds	Low, med, high,auto		
	Filter	MERV 3		
Outdoor	Туре	ECM centrifugal		
	CFM	200-350		
	Available ESP	0.25" WC		
	Intake			
	connection	8" round (can be reduced to 6" with an		
	Exhaust	adapter)		
	connection			

General

Compress	201			
Compres	SOF			
Refrigerant	t	Туре		R32
		Oz.		21.87
Oil		Туре		Fv50s
Туре		BLDO	twin rotary inverter	
Cantrala				
Controls				
Basic functionality			Dependent on controller	
WiFi			Optional module available	
Dry contact			Yes	
Modes				
Operation		Cool, heat dehumidify, auto		
Restricted modes		Heat only, cool only, temperature limiting		
Timers		Dependent on controller		
Condensa	ate			
Pipe	Size		3/4" Outside diameter	
	Material		Rubber	

Sound

Sound		
	dB(A)	27-41
Indoor	STC	37
	OITC	28
Outdoor	dB(A)	28-52

Dimensions

Physical data					
Dimensions	Net	39.7 "W x 21.9" H x 6.5" D			
Waight	Net	100 lb			
Weight	Gross	105 lb			
	Finish	RAL 9003 signal white			
Cabinet	Material	Steel			