

## Electrical

### General

|                        |                    |      |  |
|------------------------|--------------------|------|--|
| Volt range             | 180-253            |      |  |
| Hz/phase               | 60 Hz single phase |      |  |
| Power supply           | Hardwire or LCDI   |      |  |
| Power factor (%)       | 0.96               |      |  |
| Input power (standby)  | W                  | 10.8 |  |
| Input power (off mode) |                    | 1.5  |  |
| Cooling (nominal)      | A                  | 2.9  |  |
| Cooling (max)          |                    | 7.8  |  |
| Heating (nominal)      |                    | 3.1  |  |
| Heating (max)          | 8.3                |      |  |

### Motors

|                       |         |      |     |
|-----------------------|---------|------|-----|
| Compressor            | RLA     | A    | 4.7 |
|                       | LRA     |      |     |
| Indoor ECM fan motor  | W (max) | 180  |     |
|                       | F.L.A.  | A    | 0.8 |
|                       | HP      | 0.24 |     |
| Outdoor ECM fan motor | W (max) | 190  |     |
|                       | F.L.A.  | A    | 0.8 |
|                       | HP      | 0.25 |     |

### Circuit breakers

|                          |   |    |
|--------------------------|---|----|
| MCA                      |   | 10 |
| Recommended breaker size | A | 15 |
| MOCP                     |   | 20 |

### LCDI Power Cord

|           |       |  |
|-----------|-------|--|
| Amps      | 15    |  |
| Plug Type | 6-15P |  |