Airflow

Fresh air volume					
Indoor	Туре	ECM centrifugal			
	CFM	160-290			
	Supply connection	Integrated front			
	Return connection	Integrated bottom			
	Speeds	Low, med, high,auto			
	Filter	MERV 3			
Outdoor	Туре	ECM centrifugal			
	CFM	200-350			
	Available ESP	0.25" WC			
	Intake				
	connection	8" round (can be reduced to 6" with an			
	Exhaust	adapter)			
	connection				

General

Compressor				
Defricerent	Туре		R32	
Refrigerant	Oz.		21.87	
Oil	Туре		Fv50s	
Туре	BLDC twi	n rotary inverter		
Controls				
Basic functionality		Dependent on controller		
WiFi		Optional module available		
Dry contact		Yes		
Modes				
Operation Coo		, heat dehumidify, auto		
Restricted modes Heat		only, cool only, temperature limiting		
Timers	Deper	Dependent on controller		
Condensate				
Size		3/4" Outside diameter		
Pipe Materia	ıl	Rubber		

Sound

Sound					
	dB(A)	27-41			
Indoor	STC	37			
	OITC	28			
Outdoor	dB(A)	28-52			

Dimensions

Physical data					
Dimensions	Net	39.7 "W x 21.9" H x 6.5" D			
	Net	100 lb			
Weight	Gross	105 lb			
	Finish	RAL 9003 signal white			
Cabinet	Material	Steel			